| SPECIFICATION SHEET - 02A  02A VMI, Inc. Blower unit, Individual Specifications Dated April 10, 2013 |  |
|--|--|
|  |  |
| Safety Standards   | C-UL-US Listed   |
| Dimensions   |  |
| Front Panel  | 13 3/4" Deep x 19 3/4" Wide  |
| Housing  | 11 3/8" Deep x 17 3/8" Wide x 8 1/4" High (with Damper, 10 3/4" High)          |
| Weight   | 18 lbs   |
| Rated Voltage  | 120 Volts  |
| Rated Frequency  | 60 Hz  |
| Air Flow   | High Speed Operating 390 CFM   |
|  | Medium Speed Operating 290 CFM   |
| *  | Low Speed Operating 180 CFM  |
| Noise Level  | High Speed Motor 7 Sones   |
|  | Medium Speed Motor 5 Sones   |
|  | Low Speed Motor 3 Sones  |
| Power Consumption  | High Speed 120 Watts   |
| Motor Only   | Medium Speed 90 Watts  |
|  | Low Speed 60 Watts   |
| Electric Motor   | Capacitor Motor, 3 Speeds  |
| Duct Dimension   | 7" Round Duct  |
| Exhaust Direction  | Vertical Discharge from top, Horizontal with Elbow                             |
| Installation   | At 4 places on flange of body, use screws and nut plates for mounting to Liner |
| Materials  | Front Cover Panel - 304 Grade Stainless Steel, # 4 Brush Finish                |
|  | Housing Body - Electro-Galvanized steel  |
|  | Filters - Aluminum Mesh  |
|  | *Front Cover Panel Colors -Silver Metallic, White, Bisquit, Black              |
| Lighting   | (1) 50 watt MR16-GU10 Halogen Lamp   |
| Switches   | Mechanical Push Button 3 Speed with Off Motor Control                          |
|  | Mechanical Push Button Light Control   |
| Electrical Wiring  | PVC, 18 AWG  |
| Accessories  | Damper, Nut Plates with screws   |
| Optional Parts   | Metal Liners, Rectangular, T-Shaped, Custom Sized                              |
| Manual   | Installation/Operation Manual  |