SPECIFICATION SHEET - 04	
04	VMI, Inc. Blower unit, Individual Specifications Dated April 10, 2013
Model	04 Powder Coat Painted Front Cover Panel*
Safety Standards	C-UL-US Listed
Dimensions	
Front Panel	13 3/4" Deep x 19 3/4" Wide
Housing	11 3/8" Deep x 17 3/8" Wide x 3 3/8" High (with Damper, 5 1/8" High)
Weight	11 lbs
Rated Voltage	120 Volts
Rated Frequency	60 Hz
Air Flow	High Speed Operating 280 CFM
	Low Speed Operating 180 CFM
Noise Level	High Speed Motor 7 Sones Low Speed Motor 3 Sones
	Low Speed Motor 3 Solles
Power Consumption	High Speed 90 Watts
Motor Only	low Speed 65 Watts
Electric Motor	Capacitor Motor, 2 Speeds
Duct Dimension	7" Round Duct
Exhaust Direction	Vertical Discharge from top, Horizontal with Elbow
Installation	At 4 places on flange of body, use screws and nut plates for mounting to Liner
Materials	Front Cover Panel - Powder Coated Painted Finish
	Housing Body - Electro-Galvanized steel
	Filters - Aluminum Mesh
	*Front Cover Panel Colors -Silver Metallic, White, Bisquit, Black
Lighting	(1) 50 watt MR16-GU10 Halogen Lamp
Switches	Mechanical Push Button 2 Speed with Off Motor Control
	Mechanical Push Button Light Control
Electrical Wiring	PVC, 18 AWG
Accessories	Damper, Nut Plates with screws
Optional Parts	Metal Liners, Rectangular, T-Shaped, Custom Sized
Manual	Installation/Operation Manual