SPECIFICATION SHEET - 06 W/P 06 W/P VMI, Inc. Blower unit, Individual Specifications Dated April 10, 2013	
Safety Standards	C-UL-US Listed
Dimensions	
Front Panel	16 3/4" Deep x 26 3/4" Wide
Housing Height	10" High (with Damper, 10 1/2" High)
Weight	25 lbs
Rated Voltage	120 Volts
Rated Frequency	60 Hz
Air Flow	High Speed Operating 660 CFM
	Medium Speed Operating 320 CFM
	Low Speed Operating 240 CFM
Noise Level	High Speed Motor 7.5 Sones
	Medium Speed Motor 4.0 Sones
	Low Speed Motor 3.0 Sones
Power Consumption	High Speed 240 Watts
Motor Only	Medium Speed 144 Watts
	Low Speed 134 Watts
Electric Motor	Capacitor Motor, 3 Speeds
Duct Dimension	8" Round Duct
Exhaust Direction	Vertical Discharge from top, Horizontal with Elbow
Installation	At 4 places on flange of body, use screws and nut plates for mounting to Liner
	Wall mount with brackets provided, Island with threaded rod, not provided
Materials	Front Cover Panel - 304 Grade Stainless Steel, # 4 Brush Finish
	Housing Body - Electro-Galvanized steel
	Filters - Aluminum Mesh
Lighting	(2) 50 watt MR16-GU10 Halogen Lamps
Switches	Mechanical Push Button 3 Speed with Off Motor Control
	Mechanical Push Button Light Control
Electrical Wiring	PVC, 18 AWG
Accessories	Damper, Nut Plates, Island Mount Panel, Wall Brackets
Optional Parts	Metal Liners, Rectangular, T-Shaped, Custom Sized
Manual	Installation/Operation Manual