# CL400<sup>®</sup>ADA Magnetic - Offset

The new **CL400® ADA Magnetic** matches the look and functionality of the existing CL400 Magnetic range of pocket door hardware, with added ADA functionality.

Utilizing the patented magnetic mechanism of the CL400 Magnetic, this new addition to the range provides flexibility for building owners. The CL400 ADA uses the same door cutout and striker and is able to be retrofitted over existing CL400 flush handles for the requirements of ADA tenants.

The CL400 ADA is compatible with egress applications.





CaviLock CL400 ADA Privacy with Emergency Release



CL400 ADA Privacy Snib in satin nickel finish.



Quality Sliding Door Hardware

## CL400<sup>®</sup> ADA Magnetic - Offset



In line with ADA Standards for Accessible Design, the CL400 ADA Magnetic has a handle that is easy to grasp with one hand and does not require tight grasping, tight pinching or twisting of the wrist.

The opening force required to operate the unit is 2.5lbf (11.1N), which is under the 5lbf threshold for ADA compliance.

### **Design Features & Options**

- Easy to use no tight pinching or twisting of the wrist.
- See at a glance whether a room is occupied.
- Patented magnetic functionality.
- Striker sits flush with closing jamb.

#### **Dimensions**

- Matches other hardware in the CL400 range.

1-3/8'

#### Finish Options



Satin Chrome Chrome


Satin Nickel


Oil Rubbed Bronze

Other finish options available on request. (Note: Longer lead times and additional surcharges may apply.)

Ũ

## **Configuration Options**





Privacy

5<sup>7/8″</sup>


(149mm)


27/32"


(56.5mm)

Emergency Release

**Bi-Parting** (Passage or Privacy)







Passage

**IMPORTANT:** Operable parts of hardware must be mounted 34" (865mm) min. and 48" (1220 mm) max. above finished floor to meet ADA guidelines.

The clear width of the door opening must be a minimum of 32". Always check State and Federal guidelines relating to the specific project.

Selection Procedure To order, ensure you have the following information ready:

Function	Finish	Door thickness	Handing Configuration
Single Door	Satin Chrome	1-3/8" to 1-9/16"	Handing must be determined at time of manufacture and cannot be altered on site. Careful selection of handing options is required at
Bi-Parting Door	Satin Nickel	1-5/8" to 1-3/4"	time of order. See diagram for determining handing of functions.
Passage (Non Latching)	Bright Chrome	1-13/16" to 2"	LH RH Stand looking into the pocket as
Passage (Mag Latching)	ORB	2-1/16" to 2-1/4"	Blank Blank Snib
Privacy Locking	Special Order		Emerg Emerg

Drawings & pictures are not to scale. Colors shown may not accurately represent product All dimensions in inches (and mm).

#### www.cavitysliders.com

High quality products designed in New Zealand

- T (888) 466 0030 F.
  - (310) 769 5824
  - E info@cavitysliders.com

#### **Cavity Sliders USA Inc.**





CAVILOCK® CL400® ADA OFFSET (0.D. 2017). 61225 - 11.2017